

<u>Regulated States</u>	<u>Standard</u>	<u>Sampling Requirements</u>	<u>Technology Based Standard</u>
Arkansas	0.05/100cm <sup>2</sup>	400/cm <sup>2</sup> per room + Fixtures	Yes
<b>Arizona</b>	<b>1.50/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
North Carolina	0.10/100cm <sup>2</sup>	Per Consultant	Yes
<b>West Virginia</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Kentucky	0.10/100cm <sup>2</sup>	400/cm <sup>2</sup> per room + Fixtures	Yes – May require encapsulation
<b>Tennessee</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Indiana	0.50/100cm <sup>2</sup>	400/cm <sup>2</sup> per room + Fixtures	Yes
<b>Michigan</b>	<b>0.50/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Minnesota - Lab Site	0.10/100cm <sup>2</sup>	Per Consultant with approval	Yes
Minnesota - Use Site	1.50/100cm <sup>2</sup>	Per Consultant with approval	Requires Encapsulation or defaults to 0.1ug/100cm <sup>2</sup>
<b>Oklahoma</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Based on State Disclosure Law</b>
Oregon	0.50/1ft <sup>2</sup>	3Ftz, Discrete Only, Floors Only	Yes
<b>Washington</b>	<b>1.50/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Idaho	0.10/100cm <sup>2</sup>	300/cm <sup>2</sup> in lab room - 100/cm <sup>2</sup> all other rooms	Yes
<b>Hawaii</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Alaska	0.10/100cm <sup>2</sup>	Per Consultant	Yes
<b>New Mexico</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Montana	0.10/100cm <sup>2</sup>	Per Consultant with approval	Yes
<b>South Dakota</b>	<b>0.10/100cm<sup>2</sup></b>	<b>Per Consultant</b>	<b>Yes</b>
Nebraska	0.10/100cm <sup>2</sup>	600/cm <sup>2</sup> per room	Yes

<b>Colorado</b>	<b>0.50/100cm<sup>2</sup> 4.0ug/100cm<sup>2</sup> 1.5ug/100cm<sup>2</sup></b>	<b>400/cm<sup>2</sup> per room Attics and Crawl Spaces Pre Encapsulated surfaces</b>	<b>Health Based Standard</b>
Wyoming	0.75/100cm <sup>2</sup>	Minimum 15 samples	yes
<b>Utah</b>	<b>1.00/100cm<sup>2</sup></b>	<b>300/cm<sup>2</sup> per room</b>	<b>Health Based Standard</b>
California	1.50/100cm <sup>2</sup>	400/cm <sup>2</sup> per room + Fixtures	<b>Health Based Standard</b>

Standard practice in states that do not dictate the sampling frequency by rule is 300 to 400 cm<sup>2</sup> per functional space.

Current analytical methods most commonly utilized are EPA SW846, 8270D or 8270 C (modified) GC/MS, or NIOSH 9111 (modified) LC/MS.

All of these methods are formulated to 100cm<sup>2</sup> sampling parameters not to exceed 400cm<sup>2</sup> in any one sample.

Discrete 100cm<sup>2</sup> samples are reported in actual concentration of ug per sample.

Composite sample results are reported in total ug results and interpolated and reported in ug/100cm<sup>2</sup> for theoretical averages (total divided by number of aliquots).

The concentration per 100cm<sup>2</sup> or the interpolated average is used to determine if a sample or the space where the sample was collected is compliant.

Typical sample collection for preliminary and/or post remediation sampling is either one composite sample of no more than 4 aliquots per functional space or 3-4 discrete samples per functional space. Either is acceptable in all regulated states.

Functional spaces are considered any area in excess of 150 square feet in size.

No state or federal certification is required for laboratories providing methamphetamine analysis.